



# TrueLine, recessed - True line of light: elegant, energy- efficient and compliant with office lighting norms

## TrueLine, recessed

Architects need a lighting solution that matches the interior architecture of the property they are working on. They want a light line with an elegant design and very high light levels. Specifiers need luminaires that enable them to save energy while at the same time providing the right level of light, in compliance with office lighting norms. TrueLine, recessed is able to meet both sets of requirements. TrueLine is also available in suspended and surface-mounted versions.

### Benefits

- The most uniform exit window
- Extremely high efficacy for a line luminaire
- Luminaire housing dimensions that are most popular with architects

## Features

- Luminous efficacy > 100 lm/W
- Complies with office lighting norms
- Stand-alone and continuous lines
- Suspended version also available
- Direct and indirect light
- Homogeneous exit window
- Future-proof: PoE

## Application

- General lighting for mid- and high-end office buildings

## Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that The environment in which The luminaire is to be installed is suitably checked
- If The above advice is not taken and The luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

## Specifications

|                     |                                                             |
|---------------------|-------------------------------------------------------------|
| <b>Type</b>         | SP530P (office compliant direct-light version)              |
|                     | SP531P (non-office compliant direct-light version)          |
|                     | SP532P (office compliant direct/indirect-light version)     |
|                     | SP533P (non-office compliant direct/indirect-light version) |
| <b>Light source</b> | Non-replaceable LED module                                  |


|              |                                                               |
|--------------|---------------------------------------------------------------|
| <b>Power</b> | Office compliant (OC), 1130 and 1170 mm, 4000 K versions:     |
|              | 10 W (direct 1500 lm)                                         |
|              | 17.5 W (direct 2500 lm)                                       |
|              | 24 W (direct 3400 lm)                                         |
|              | 29 W (direct 4000 lm)                                         |
|              | 15.2 W (direct 1500 lm, indirect 660 lm, total 2160 lm)       |
|              | 25.5 W (direct 2500 lm, indirect 1100 lm, total 3600 lm)      |
|              | 35.5 W (direct 3400 lm, indirect 1550 lm, total 4950 lm)      |
|              | 42.5 W (direct 4000 lm, indirect 1850 lm, total 5850 lm)      |
|              | Non-office compliant (NOC) 1130 and 1170 mm, 4000 K versions: |
|              | 14.6 W (direct 1500 lm)                                       |
|              | 24.5 W (direct 2500 lm)                                       |
|              | 21 W (direct 1500 lm, indirect 940 lm, total 2440 lm)         |
|              | 36 W (direct 2500 lm, indirect 1600 lm, total 4100 lm)        |
|              | Office compliant (OC) 1410 and 1450 mm, 4000 K versions:      |
|              | 12.4 W (direct 1900 lm)                                       |
|              | 21.5 W (direct 3100 lm)                                       |
|              | 32 W (direct 4300 lm)                                         |
|              | 38.5 W (direct 5000 lm)                                       |
|              | 19.2 W (direct 1900 lm, indirect 1000 lm, total 2900 lm)      |
|              | 34 W (direct 3100 lm, indirect 1650 lm, total 4750 lm)        |
|              | 50 W (direct 4300 lm, indirect 2300 lm, total 6600 lm)        |
|              | 60 W (direct 5000 lm, indirect 2700 lm, total 7700 lm)        |
|              | Non-office compliant (OC) 1410 and 1450 mm, 4000 K versions:  |
|              | 17.8 W (direct 1900 lm)                                       |
|              | 32 W (direct 3100 lm)                                         |
|              | 29 W (direct 1900 lm, indirect 1400 lm, total 3300 lm)        |
|              | 51 W (direct 3100 lm, indirect 2300 lm, total 5400 lm)        |
|              | Office compliant (OC) 1130 and 1170 mm, 3000 K versions:      |
|              | 10.6 W (direct 1500 lm)                                       |
|              | 18.2 W (direct 2500 lm)                                       |

## TrueLine, recessed

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
|                              | 25.5 W (direct 3400 lm)                                      |
|                              | 30.5 W (direct 4000 lm)                                      |
|                              | 16 W (direct 1500, indirect 660, total 2160 lm)              |
|                              | 26.5 W (direct 2500, indirect 1100, total 3600 lm)           |
|                              | 37.5 W (direct 3400, indirect 1550, total 4950 lm)           |
|                              | 44.5 W (direct 4000, indirect 1850, total 5850 lm)           |
|                              | Non-office compliant (NOC) 1130 and 1170mm, 3000 K:          |
|                              | 15.6 W (direct 1500 lm)                                      |
|                              | 26 W (direct 2500 lm)                                        |
|                              | 22 W (direct 1500 lm, indirect 940 lm, total 2440 lm)        |
|                              | 38.5 W (direct 2500 lm, indirect 1600 lm, total 4100 lm)     |
|                              | Office compliant (OC) 1410 and 1450 mm, 3000 K versions:     |
|                              | 13 W (direct 1900 lm)                                        |
|                              | 23 W (direct 3100 lm)                                        |
|                              | 34 W (direct 4300 lm)                                        |
|                              | 40.5 W (direct 5000 lm)                                      |
|                              | 20 W (direct 1900 lm, indirect 1000 lm, total 2900 lm)       |
|                              | 36 W (direct 3100 lm, indirect 1650 lm, total 4750 lm)       |
|                              | 53 W (direct 4300 lm, indirect 2300 lm, total 6600 lm)       |
|                              | 64 W (direct 5000 lm, indirect 2700 lm, total 7700 lm)       |
|                              | Non-office compliant (OC) 1410 and 1450 mm, 3000 K versions: |
|                              | 18.8 W (direct 1900 lm)                                      |
|                              | 34 W (direct 3100 lm)                                        |
|                              | 31 W (direct 1900 lm, indirect 1400 lm, total 3300 lm)       |
|                              | 55 W (direct 3100 lm, indirect 2300 lm, total 5400 lm)       |
| <b>Beam angle</b>            | 80 ° (OC), 110 ° (NOC)                                       |
| <b>Luminous flux</b>         | 1500 to 7700 lm (4000 K)                                     |
| <b>Correlated Color</b>      | 3000 or 4000 K                                               |
| <b>Temperature</b>           |                                                              |
| <b>Color Rendering Index</b> | >80                                                          |
| <b>Lumen maintenance at</b>  | L85                                                          |
| <b>median useful life*</b>   | 50000 h                                                      |

|                                  |                                                                                                                                                                              |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Control gear failure rate</b> | 5%                                                                                                                                                                           |
| <b>at median useful life</b>     |                                                                                                                                                                              |
| <b>50000 h</b>                   |                                                                                                                                                                              |
| <b>Performance Ambient</b>       | +25 °C                                                                                                                                                                       |
| <b>Temperature Tq</b>            |                                                                                                                                                                              |
| <b>Operating temperature</b>     | +10 to +40 °C                                                                                                                                                                |
| <b>range</b>                     |                                                                                                                                                                              |
| <b>Driver</b>                    | Built-in                                                                                                                                                                     |
| <b>Power/Data supply</b>         | PDS-60 24 V; supply for indoor and outdoor applications                                                                                                                      |
| <b>Mains voltage</b>             | 220-240 V / 50-60 Hz                                                                                                                                                         |
| <b>Dimming</b>                   | Compatible with many commercial available ELV dimmers                                                                                                                        |
| <b>Controls system input</b>     | 0-16 V, DALI                                                                                                                                                                 |
| <b>Options</b>                   | Central battery                                                                                                                                                              |
| <b>Material</b>                  | Housing: anodized aluminum                                                                                                                                                   |
|                                  | Driver box: steel                                                                                                                                                            |
|                                  | Cover: PMMA or polycarbonate                                                                                                                                                 |
| <b>Color</b>                     | Aluminum (ALU)                                                                                                                                                               |
| <b>Optical cover</b>             | Office compliant: PMMA, semi-transparent                                                                                                                                     |
|                                  | Non-office compliant: polycarbonate, opal                                                                                                                                    |
| <b>Connection</b>                | Push-in connector (PI) or with pull relief (PIP)                                                                                                                             |
| <b>Maintenance</b>               | Optical module replaceable, no internal cleaning required                                                                                                                    |
| <b>Installation</b>              | Fixation by means of brackets                                                                                                                                                |
|                                  | Individual or in line; suspended mounting with three different options:                                                                                                      |
|                                  | SM2 (one 2-wire bag, one Reutlinger for ceiling side, one ceiling cap)                                                                                                       |
|                                  | SW2 (one 2-wire bag, one (for LF1) or two (for BV/LE1) Reutlingers, one tool to fix the alignment profile (for LF1))                                                         |
|                                  | SMTT (one 2-wire bag, one (for LF1) or two (for BV/LE1) T-bar ceiling clips, one (for LF1) or two (for BV/LE1) Reutlingers, one tool to fix the alignment profile (for LF1)) |
|                                  | Through-wiring possible                                                                                                                                                      |
| <b>Remarks</b>                   | Suspension set to be delivered with the luminaire                                                                                                                            |

## Versions



Trueline recessed RC530B luminaire, standalone office-compliant version, 1.2 m



TrueLine Recessed Standalone Asym

TrueLine, recessed

Versions



Trueline recessed RC532B  
luminaire, line feature office-  
compliant version, 1.2 m



TrueLine Recessed Line Asym -  
LED module, system flux 3400 lm  
- 1130 mm



TrueLine Recessed Line OC



RC530B



RC530B



TrueLine\_Recessed-U0



TrueLine Recessed OC - 930 warm  
white - Power supply unit with  
DALI and SystemReady interface,  
InterAct ready - Push-in connector  
3-pole - White RAL 9003

Product details

TrueLine\_recessed-  
RC530B\_PCV\_L1130-DP.tif



TrueLine-  
RC530\_RC531\_RC534B\_VPC-  
DPP.tif



TrueLine-  
RC530\_RC531\_RC534B\_VPC\_PI5-  
DPP.tif



TrueLine-  
RC530\_RC531\_RC532\_RC533B\_P  
CV-1DPP.tif



TrueLine-  
RC530\_RC531\_RC532\_RC533B\_P  
CV-2DPP.tif



TrueLine-  
RC532\_RC533B\_ELP3-1DPP.tif



TrueLine-  
RC532\_RC533B\_ELP3-2DPP.tif



TrueLine-  
RC534B\_SM534C\_SP534P-DPP.tif



Product details

TrueLine\_Recessed-U0



TrueLine\_accessories\_U5-DP



TrueLine\_accessories\_U6-DP



TrueLine\_accessories\_U4-DP



TrueLine\_Recessed-U3



Accessories

TrueLine ACC - End piece - White  
- Set of 2 units



Ordercode 910403219703

TrueLine Accessories - - V - - Hz  
- - - - - White



Ordercode 910505101357

Accessories



TrueLine Accessories - V - - Hz  
- - - - - White

Ordercode 910505101358



TrueLine Accessories - V - - Hz  
- - - - - White

Ordercode 910505101359



TrueLine Accessories - V - - Hz  
- - - - - White

Ordercode 910505101665

### Application conditions

|                               |               |
|-------------------------------|---------------|
| Ambient temperature range     | +10 to +40 °C |
| Maximum dim level             | 1%            |
| Suitable for random switching | No            |

### Approval and application

|                              |      |
|------------------------------|------|
| Mech. impact protection code | IK02 |
| Ingress protection code      | IP20 |

### Controls and dimming

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

### Operating and electrical

|               |              |
|---------------|--------------|
| Input Voltage | 220 to 240 V |
|---------------|--------------|

### General information

|                          |                                             |
|--------------------------|---------------------------------------------|
| CE mark                  | CE mark                                     |
| Driver included          | Yes                                         |
| ENEC mark                | ENEC mark                                   |
| Flammability mark        | For mounting on normally flammable surfaces |
| Glow-wire test           | Temperature 650 °C, duration 30 s           |
| Light source replaceable | No                                          |
| Number of gear units     | 1 unit                                      |
| Optic type               | -                                           |

### Initial performance (IEC compliant)

|                             |                      |
|-----------------------------|----------------------|
| Initial chromaticity        | (0.38, 0.38) SDCM <3 |
| Init. Color Rendering Index | >90                  |
| Luminous flux tolerance     | +/-10%               |

### Light technical

|                     |     |
|---------------------|-----|
| Flickering          | 1   |
| Stroboscopic effect | 0.4 |

### Mechanical and housing

|       |                |
|-------|----------------|
| Color | White RAL 9003 |
|-------|----------------|

### General information

| Order Code   | Full Product Name                        | Beam angle of light source | Protection class IEC | Product Family Code |
|--------------|------------------------------------------|----------------------------|----------------------|---------------------|
| 910505103101 | RC530B LED43S/940 PSD W8L150 VPC PI5 IP  | - °                        | Safety class I       | RC530B              |
| 910505103102 | RC532B LED25S/940 PSD W8L113 VPC PI5     | - °                        | Safety class I       | RC532B              |
| 910505103103 | RC531B LED19S/930 PSD W8L150 VPC PI5 IP  | - °                        | Safety class I       | RC531B              |
| 910505103104 | RC530B LED15S/940 PSD W8L113 PCV PI5     | - °                        | Safety class I       | RC530B              |
| 910505103105 | RC530B LED34S/930 PSD W8L120 VPC PI5 IP  | - °                        | Safety class I       | RC530B              |
| 910505103106 | RC532B LED19S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC532B              |
| 910505103107 | RC530B LED31S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC530B              |
| 910505103109 | RC533B LED15S/940 PSD W8L113 PCV PI5     | - °                        | Safety class I       | RC533B              |
| 910505103110 | RC530B LED43S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC530B              |
| 910505103111 | RC531B LED15S/940 PSD W8L120 VPC PI5 IP  | - °                        | Safety class I       | RC531B              |
| 910505103112 | RC531B LED15S/930 PSD W8L120 VPC PI5 IP  | - °                        | Safety class I       | RC531B              |
| 910505103113 | RC530B LED50S/940 PSD W8L150 VPC PI5 IP  | - °                        | Safety class I       | RC530B              |
| 910505103114 | RC530B LED19S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC530B              |
| 910505103115 | RC530B LED34S/940 PSD W8L113 PCV PI5     | - °                        | Safety class I       | RC530B              |
| 910505103116 | RC531B LED15S/930 PSD W8L113 PCV PI5     | - °                        | Safety class I       | RC531B              |
| 910505103117 | RC531B LED15S/940 PSD W8L113 PCV PI5     | - °                        | Safety class I       | RC531B              |
| 910505103118 | RC532B LED15S/940 PSD W8L113 PCV PI5     | - °                        | Safety class I       | RC532B              |
| 910505103119 | RC532B LED25S/940 PSD W8L113 PCV PI5     | - °                        | Safety class I       | RC532B              |
| 910505103121 | RC531B LED31S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC531B              |
| 910505103126 | RC533B LED31S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC533B              |
| 910505103127 | RC530B LED50S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC530B              |
| 910505103129 | RC531B LED19S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC531B              |
| 910505103131 | RC533B LED19S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC533B              |
| 910505103149 | RC530B LED40S/940 PSD W8L120 VPC PI5     | - °                        | Safety class I       | RC530B              |
| 910505103150 | RC530B LED34S/940 PSD W8L120 VPC PI5 IP  | - °                        | Safety class I       | RC530B              |
| 910505103284 | RC530B LED34S/TW9 DIA W8L113 PCV PI5     | 120 °                      | Safety class I       | RC530B              |
| 910505103286 | RC530B LED40S/TW9 DIA W8L113 PCV PI5     | 120 °                      | Safety class I       | RC530B              |
| 910505103287 | RC530B LED50S/TW9 DIA W8L145 PCV PI5     | 120 °                      | Safety class I       | RC530B              |
| 910505103292 | RC530B LED34S/940 PSD W8L113 PCV PI5 SC  | 120 °                      | Safety class I       | RC530B              |
| 910505103293 | RC530B LED34S/940 PSD W8L120 VPCPI5 IPSC | 120 °                      | Safety class I       | RC530B              |
| 910505103120 | RC534B LED40S/940 PSD W8L120 VPC PI5 IP  | - °                        | Safety class I       | RC534B              |
| 910505103123 | RC534B LED50S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC534B              |
| 910505103128 | RC534B LED43S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC534B              |
| 910505103122 | RC532B LED31S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC532B              |
| 910505103124 | RC532B LED43S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC532B              |

| Order Code   | Full Product Name                        | Beam angle of light source | Protection class IEC | Product Family Code |
|--------------|------------------------------------------|----------------------------|----------------------|---------------------|
| 910505103125 | RC535B LED50S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC535B              |
| 910505103130 | RC535B LED43S/940 PSD W8L141 PCV PI5     | - °                        | Safety class I       | RC535B              |
| 910505103132 | RC532B LED43S/940 W8L145 VPC ELP3 W      | - °                        | Safety class I       | RC532B              |
| 910505103133 | RC532B LED19S/940 W8L145 VPC ELP3 W      | - °                        | Safety class I       | RC532B              |
| 910505103134 | RC533B LED19S/940 W8L145 VPC ELP3 W      | - °                        | Safety class I       | RC533B              |
| 910505103137 | RC532B LED31S/940 W8L145 VPC ELP3 W      | - °                        | Safety class I       | RC532B              |
| 910505103142 | RC532B LED50S/940 W8L145 VPC ELP3 W      | - °                        | Safety class I       | RC532B              |
| 910505103143 | RC533B LED31S/940 PSD W8L145 VPC ELP3 W  | - °                        | Safety class I       | RC533B              |
| 910505103135 | RC530B LED43S/940 W8L145 PCV ELP3 PI6    | - °                        | Safety class I       | RC530B              |
| 910505103136 | RC530B LED50S/940 W8L145 PCV ELP3 PI6    | - °                        | Safety class I       | RC530B              |
| 910505103139 | RC531B LED19S/940 W8L145 PCV ELP3 PI6    | - °                        | Safety class I       | RC531B              |
| 910505103145 | RC531B LED31S/940 W8L145 PCV ELP3 PI6    | - °                        | Safety class I       | RC531B              |
| 910505103153 | RC531B LED19S/940 PSD W8L145 PCV ELD3PI6 | - °                        | Safety class I       | RC531B              |
| 910505103138 | RC531B LED31S/940 W8L150 VPC ELP3 PI6    | - °                        | Safety class I       | RC531B              |
| 910505103140 | RC531B LED19S/940 W8L150 VPC ELP3 PI6    | - °                        | Safety class I       | RC531B              |
| 910505103141 | RC530B LED50S/940 W8L150 VPC ELP3 PI6    | - °                        | Safety class I       | RC530B              |
| 910505103144 | RC530B LED43S/940 W8L150 VPC ELP3 PI6    | - °                        | Safety class I       | RC530B              |
| 910505103151 | RC533B LED19S/940 PSD W8L145 VPC ELD3 W  | - °                        | Safety class I       | RC533B              |
| 910505103152 | RC532B LED43S/940 PSD W8L145 VPC ELD3 W  | - °                        | Safety class I       | RC532B              |
| 910505103154 | RC530B LED43S/940 PSD W8L150 VPC ELD3PI6 | - °                        | Safety class I       | RC530B              |
| 910505103147 | RC530B LED40S/940 POE W8L120 VPC U0      | - °                        | Safety class III     | RC530B              |
| 910505103148 | RC530B LED40S/940 POE W8L120 VPC U3      | - °                        | Safety class III     | RC530B              |
| 910505103155 | RC532B LED43S/940 SRD W8L145 PCV U4 W    | - °                        | Safety class I       | RC532B              |
| 910505103156 | RC530B LED34S/940 SRD W8L120 VPC U4PI3SC | - °                        | Safety class I       | RC530B              |
| 910505103157 | RC530B LED34S/930 SRD W8L120 VPC U4 W    | - °                        | Safety class I       | RC530B              |
| 910505103158 | RC530B LED34S/930 SRD W8L120 VPC U4 W SC | - °                        | Safety class I       | RC530B              |
| 910505103159 | RC530B LED25S/930 SRD W8L120 VPC U4 W    | - °                        | Safety class I       | RC530B              |
| 910505103160 | RC530B LED43S/940 SRD W8L145 PCV U4 PI3  | - °                        | Safety class I       | RC530B              |

| Order Code   | Full Product Name                        | Beam angle of light source | Protection class IEC | Product Family Code |
|--------------|------------------------------------------|----------------------------|----------------------|---------------------|
| 910505103285 | RC530B LED43S/TW9 SIA W8L145 PCV U4 PI3  | 120 °                      | Safety class I       | RC530B              |
| 910505103288 | RC530B LED34S/TW9 SIA W8L120 VPC U4 PI3  | 120 °                      | Safety class I       | RC530B              |
| 910505103289 | RC530B LED43S/TW9 SIA W8L145VPC U4 PI3SC | 120 °                      | Safety class I       | RC530B              |
| 910505103290 | RC531B LED25S/TW9 SIA W8L120 VPC U4 PI3  | 120 °                      | Safety class I       | RC534B              |
| 910505103291 | RC530B LED43S/TW9 SIA W8L145PCV U4 PI3SC | 120 °                      | Safety class I       | RC530B              |

### Initial performance (IEC compliant)

| Order Code   | Full Product Name                       | Init. Corr. Color Temperature | Initial LED luminaire efficacy | Initial luminous flux | Initial input power | Order Code   | Full Product Name                       | Init. Corr. Color Temperature | Initial LED luminaire efficacy | Initial luminous flux | Initial input power |
|--------------|-----------------------------------------|-------------------------------|--------------------------------|-----------------------|---------------------|--------------|-----------------------------------------|-------------------------------|--------------------------------|-----------------------|---------------------|
| 910505103101 | RC530B LED43S/940 PSD W8L150 VPC PI5 IP | 4000 K                        | 141 lm/W                       | 4300 lm               | 30.5 W              | 910505103112 | RC531B LED15S/930 PSD W8L120 VPC PI5 IP | 3000 K                        | 100 lm/W                       | 1500 lm               | 15 W                |
| 910505103102 | RC532B LED25S/940 PSD W8L113 VPC PI5    | 4000 K                        | 137 lm/W                       | 2500 lm               | 18.2 W              | 910505103113 | RC530B LED50S/940 PSD W8L150 VPC PI5 IP | 4000 K                        | 139 lm/W                       | 5000 lm               | 36 W                |
| 910505103103 | RC531B LED19S/930 PSD W8L150 VPC PI5 IP | 3000 K                        | 102 lm/W                       | 1900 lm               | 18.6 W              | 910505103114 | RC530B LED19S/940 PSD W8L141 PCV PI5    | 4000 K                        | 136 lm/W                       | 1900 lm               | 14 W                |
| 910505103104 | RC530B LED15S/940 PSD W8L113 PCV PI5    | 4000 K                        | 132 lm/W                       | 1500 lm               | 11.4 W              | 910505103115 | RC530B LED34S/940 PSD W8L113 PCV PI5    | 4000 K                        | 139 lm/W                       | 3400 lm               | 24.5 W              |
| 910505103105 | RC530B LED34S/930 PSD W8L120 VPC PI5 IP | 3000 K                        | 131 lm/W                       | 3400 lm               | 26 W                | 910505103116 | RC531B LED15S/930 PSD W8L113 PCV PI5    | 3000 K                        | 100 lm/W                       | 1500 lm               | 15 W                |
| 910505103106 | RC532B LED19S/940 PSD W8L141 PCV PI5    | 4000 K                        | 136 lm/W                       | 1900 lm               | 14 W                | 910505103117 | RC531B LED15S/940 PSD W8L113 PCV PI5    | 4000 K                        | 104 lm/W                       | 1500 lm               | 14.4 W              |
| 910505103107 | RC530B LED31S/940 PSD W8L141 PCV PI5    | 4000 K                        | 141 lm/W                       | 3100 lm               | 22 W                | 910505103118 | RC532B LED15S/940 PSD W8L113 PCV PI5    | 4000 K                        | 132 lm/W                       | 1500 lm               | 11.4 W              |
| 910505103109 | RC533B LED15S/940 PSD W8L113 PCV PI5    | 4000 K                        | 104 lm/W                       | 1500 lm               | 14.4 W              | 910505103119 | RC532B LED25S/940 PSD W8L113 PCV PI5    | 4000 K                        | 137 lm/W                       | 2500 lm               | 18.2 W              |
| 910505103110 | RC530B LED43S/940 PSD W8L141 PCV PI5    | 4000 K                        | 141 lm/W                       | 4300 lm               | 30.5 W              | 910505103121 | RC531B LED31S/940 PSD W8L141 PCV PI5    | 4000 K                        | 107 lm/W                       | 3100 lm               | 29 W                |
| 910505103111 | RC531B LED15S/940 PSD W8L120 VPC PI5 IP | 4000 K                        | 104 lm/W                       | 1500 lm               | 14.4 W              | 910505103126 | RC533B LED31S/940 PSD W8L141 PCV PI5    | 4000 K                        | 107 lm/W                       | 3100 lm               | 29 W                |

| Order Code   | Full Product Name                                 | Init. Corr.<br>Color<br>Temperature | Initial LED<br>luminaire<br>efficacy | Initial<br>luminous<br>flux | Initial<br>input<br>power |
|--------------|---------------------------------------------------|-------------------------------------|--------------------------------------|-----------------------------|---------------------------|
| 910505103127 | RC530B<br>LED50S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 139 lm/W                             | 5000 lm                     | 36 W                      |
| 910505103129 | RC531B<br>LED19S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 107 lm/W                             | 1900 lm                     | 17.8 W                    |
| 910505103131 | RC533B<br>LED19S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 107 lm/W                             | 1900 lm                     | 17.8 W                    |
| 910505103149 | RC530B<br>LED40S/940 PSD<br>W8L120 VPC PI5        | 4000 K                              | 140 lm/W                             | 4000 lm                     | 28.5 W                    |
| 910505103150 | RC530B<br>LED34S/940 PSD<br>W8L120 VPC PI5<br>IP  | 4000 K                              | 139 lm/W                             | 3400 lm                     | 24.5 W                    |
| 910505103284 | RC530B<br>LED34S/TW9 DIA<br>W8L113 PCV PI5        | Tunable white<br>2700-6500          | 124 lm/W                             | 3400 lm                     | 27.5 W                    |
| 910505103286 | RC530B<br>LED40S/TW9 DIA<br>W8L113 PCV PI5        | Tunable white<br>2700-6500          | 121 lm/W                             | 4000 lm                     | 33 W                      |
| 910505103287 | RC530B<br>LED50S/TW9 DIA<br>W8L145 PCV PI5        | Tunable white<br>2700-6500          | 120 lm/W                             | 5000 lm                     | 41.5 W                    |
| 910505103292 | RC530B<br>LED34S/940 PSD<br>W8L113 PCV PI5<br>SC  | 4000 K                              | 139 lm/W                             | 3400 lm                     | 24.5 W                    |
| 910505103293 | RC530B<br>LED34S/940 PSD<br>W8L120 VPCPI5<br>IPSC | 4000 K                              | 139 lm/W                             | 3400 lm                     | 24.5 W                    |
| 910505103120 | RC534B<br>LED40S/940 PSD<br>W8L120 VPC PI5<br>IP  | 4000 K                              | 129 lm/W                             | 4000 lm                     | 31 W                      |
| 910505103123 | RC534B<br>LED50S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 130 lm/W                             | 5000 lm                     | 38.5 W                    |
| 910505103128 | RC534B<br>LED43S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 132 lm/W                             | 4300 lm                     | 32.5 W                    |
| 910505103122 | RC532B<br>LED31S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 141 lm/W                             | 3100 lm                     | 22 W                      |
| 910505103124 | RC532B<br>LED43S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 141 lm/W                             | 4300 lm                     | 30.5 W                    |

| Order Code   | Full Product Name                                 | Init. Corr.<br>Color<br>Temperature | Initial LED<br>luminaire<br>efficacy | Initial<br>luminous<br>flux | Initial<br>input<br>power |
|--------------|---------------------------------------------------|-------------------------------------|--------------------------------------|-----------------------------|---------------------------|
| 910505103125 | RC535B<br>LED50S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 130 lm/W                             | 5000 lm                     | 38.5 W                    |
| 910505103130 | RC535B<br>LED43S/940 PSD<br>W8L141 PCV PI5        | 4000 K                              | 132 lm/W                             | 4300 lm                     | 32.5 W                    |
| 910505103132 | RC532B<br>LED43S/940<br>W8L145 VPC ELP3<br>W      | 4000 K                              | 126 lm/W                             | 4300 lm                     | 34 W                      |
| 910505103133 | RC532B<br>LED19S/940<br>W8L145 VPC ELP3<br>W      | 4000 K                              | 109 lm/W                             | 1900 lm                     | 17.4 W                    |
| 910505103134 | RC533B<br>LED19S/940<br>W8L145 VPC ELP3<br>W      | 4000 K                              | 90 lm/W                              | 1900 lm                     | 21 W                      |
| 910505103137 | RC532B<br>LED31S/940<br>W8L145 VPC ELP3<br>W      | 4000 K                              | 122 lm/W                             | 3100 lm                     | 25.5 W                    |
| 910505103142 | RC532B<br>LED50S/940<br>W8L145 VPC ELP3<br>W      | 4000 K                              | 125 lm/W                             | 5000 lm                     | 40 W                      |
| 910505103143 | RC533B<br>LED31S/940 PSD<br>W8L145 VPC ELP3<br>W  | 4000 K                              | 95 lm/W                              | 3100 lm                     | 32.5 W                    |
| 910505103135 | RC530B<br>LED43S/940<br>W8L145 PCV ELP3<br>PI6    | 4000 K                              | 126 lm/W                             | 4300 lm                     | 34 W                      |
| 910505103136 | RC530B<br>LED50S/940<br>W8L145 PCV ELP3<br>PI6    | 4000 K                              | 125 lm/W                             | 5000 lm                     | 40 W                      |
| 910505103139 | RC531B<br>LED19S/940<br>W8L145 PCV ELP3<br>PI6    | 4000 K                              | 90 lm/W                              | 1900 lm                     | 21 W                      |
| 910505103145 | RC531B<br>LED31S/940<br>W8L145 PCV ELP3<br>PI6    | 4000 K                              | 95 lm/W                              | 3100 lm                     | 32.5 W                    |
| 910505103153 | RC531B<br>LED19S/940 PSD<br>W8L145 PCV<br>ELD3PI6 | 4000 K                              | 90 lm/W                              | 1900 lm                     | 21 W                      |

| Order Code   | Full Product Name                                 | Init. Corr.<br>Color<br>Temperature | Initial LED<br>luminaire<br>efficacy | Initial<br>luminous<br>flux | Initial<br>input<br>power |
|--------------|---------------------------------------------------|-------------------------------------|--------------------------------------|-----------------------------|---------------------------|
| 910505103138 | RC531B<br>LED31S/940<br>W8L150 VPC ELP3<br>PI6    | 4000 K                              | 95 lm/W                              | 3100 lm                     | 32.5 W                    |
| 910505103140 | RC531B<br>LED19S/940<br>W8L150 VPC ELP3<br>PI6    | 4000 K                              | 90 lm/W                              | 1900 lm                     | 21 W                      |
| 910505103141 | RC530B<br>LED50S/940<br>W8L150 VPC ELP3<br>PI6    | 4000 K                              | 125 lm/W                             | 5000 lm                     | 40 W                      |
| 910505103144 | RC530B<br>LED43S/940<br>W8L150 VPC ELP3<br>PI6    | 4000 K                              | 126 lm/W                             | 4300 lm                     | 34 W                      |
| 910505103151 | RC533B<br>LED19S/940 PSD<br>W8L145 VPC ELD3<br>W  | 4000 K                              | 90 lm/W                              | 1900 lm                     | 21 W                      |
| 910505103152 | RC532B<br>LED43S/940 PSD<br>W8L145 VPC ELD3<br>W  | 4000 K                              | 126 lm/W                             | 4300 lm                     | 34 W                      |
| 910505103154 | RC530B<br>LED43S/940 PSD<br>W8L150 VPC<br>ELD3PI6 | 4000 K                              | 126 lm/W                             | 4300 lm                     | 34 W                      |
| 910505103147 | RC530B<br>LED40S/940 POE<br>W8L120 VPC U0         | 4000 K                              | 143 lm/W                             | 4000 lm                     | 28 W                      |
| 910505103148 | RC530B<br>LED40S/940 POE<br>W8L120 VPC U3         | 4000 K                              | 143 lm/W                             | 4000 lm                     | 28 W                      |
| 910505103155 | RC532B<br>LED43S/940 SRD<br>W8L145 PCV U4 W       | 4000 K                              | 143 lm/W                             | 4300 lm                     | 30 W                      |
| 910505103156 | RC530B<br>LED34S/940 SRD                          | 4000 K                              | 142 lm/W                             | 3400 lm                     | 24 W                      |

| Order Code   | Full Product Name                                 | Init. Corr.<br>Color<br>Temperature | Initial LED<br>luminaire<br>efficacy | Initial<br>luminous<br>flux | Initial<br>input<br>power |
|--------------|---------------------------------------------------|-------------------------------------|--------------------------------------|-----------------------------|---------------------------|
|              | W8L120 VPC<br>U4PI3SC                             |                                     |                                      |                             |                           |
| 910505103157 | RC530B<br>LED34S/930 SRD<br>W8L120 VPC U4 W       | 3000 K                              | 133 lm/W                             | 3400 lm                     | 25.5 W                    |
| 910505103158 | RC530B<br>LED34S/930 SRD<br>W8L120 VPC U4 W<br>SC | 3000 K                              | 133 lm/W                             | 3400 lm                     | 25.5 W                    |
| 910505103159 | RC530B<br>LED25S/930 SRD<br>W8L120 VPC U4 W       | 3000 K                              | 133 lm/W                             | 2500 lm                     | 18.8 W                    |
| 910505103160 | RC530B<br>LED43S/940 SRD<br>W8L145 PCV U4<br>PI3  | 4000 K                              | 143 lm/W                             | 4300 lm                     | 30 W                      |
| 910505103285 | RC530B<br>LED43S/TW9 SIA<br>W8L145 PCV U4<br>PI3  | Tunable white<br>2700-6500          | 121 lm/W                             | 4300 lm                     | 35.5 W                    |
| 910505103288 | RC530B<br>LED34S/TW9 SIA<br>W8L120 VPC U4<br>PI3  | Tunable white<br>2700-6500          | 124 lm/W                             | 3400 lm                     | 27.5 W                    |
| 910505103289 | RC530B<br>LED43S/TW9 SIA<br>W8L145VPC U4<br>PI3SC | Tunable white<br>2700-6500          | 121 lm/W                             | 4300 lm                     | 35.5 W                    |
| 910505103290 | RC531B<br>LED25S/TW9 SIA<br>W8L120 VPC U4<br>PI3  | Tunable white<br>2700-6500          | 93 lm/W                              | 2500 lm                     | 27 W                      |
| 910505103291 | RC530B<br>LED43S/TW9 SIA<br>W8L145PCV U4<br>PI3SC | Tunable white<br>2700-6500          | 121 lm/W                             | 4300 lm                     | 35.5 W                    |

TrueLine, recessed

